Product Specification 6525-10

6525-10 is a red Silicone Rubber/Glass Fabric with Silicone adhesive & corrugated yellow liner. It is used where preparatory Grit blast is particularly heavy. Unlike some competitors' product, Taconic's 6525-10 has a liner, which makes it easier to remove. It is a Rolls Royce Approved product available in slit rolls format at required widths.

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		**Silicone**		
Substrate Type		**E-GLASS**		
Total Weight of Substrate	g/m2	**123**		ISO 2286-2
% Coating of Substrate	%	**63**		
Substrate Nominal Thickness		**N/A**		
Adhesive Thickness	micron	**75**		ISO 2286-3
Total Product Thickness	micron	**325**		
Adhesive Strength	N/25mm	**8**	Typical	ISO 8510-2
		6	Minimum	
Operating Temperature	°Celsius	**-73° to +230°**		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.

QUALITY ISO 9001:2015 NSAI Certified
ENVIRONMENT ISO 14001:2015 NSAI Certified

Please visit our website www.taconic-ipd.com to learn more about our products and contact us on info@taconic-ipd.com for samples or a quotation.

TÜV SÜD ISO 9001

Ireland info@taconic-ipd.com
France info@taconic-ipd.fr
Germany info@taconic.de
Italy info@arcari-taconic.it
United Kingdom info@wildcat-taconic.com
Poland biuro@4taconic.com

For queries in North America please visit www.4taconic.com or email info@4taconic.com

REACH COMPLIANCE RoHS