# Product Specification 7060 LSR RED

Taconic's 7060 LSR RED is a PTFE coated glass fibre product with a super smooth PTFE content on 1 face and liquid silicone rubber on the 2nd face. The food approved high release silicone rubber side makes it ideal for use in domestic cooking applications as it will stay fixed to the surface where food preparation is taking place. The smooth PTFE surface ensures maximum release of the sticky items being handed. 7060 LSR RED offers excellent value and performance with standard width being 1000mm.

| Product Properties | Units | Value | Tolerance | Test Method |
|---|---|---|---|---|
| Reinforcing Substrate | | **E-GLASS** | | |
| Coating Type | | **LSR** | | |
| % Coating | % | **25** | +/-2% | ISO 2286-2 |
| Total Coated Weight | g/m2 | **425** | +/- 5% | ISO 2286-2 |
| Nominal Thickness | microns | **240** | | ISO 2286-3 |
| Tensile Strength | N/5cm | **1500** | Typical Warp | ISO 1421 |
| | | **1200** | Minimum Warp | |
| | | **N/A** | Typical weft | |
| | | **N/A** | Minimum weft | |
| Colour | | **Red** | | |
| Operating Temperature | °Celsius | **-73° to +230°** | | |

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.

QUALITY ISO 9001:2015 NSAI Certified
ENVIRONMENT ISO 14001:2015 NSAI Certified

Please visit our website www.taconic-ipd.com to learn more about our products and contact us on info@taconic-ipd.com for samples or a quotation.

TÜV SÜD ISO 9001

**Ireland** info@taconic-ipd.com
**France** info@taconic-ipd.fr
**Germany** info@taconic.de
**Italy** info@arcari-taconic.it
**United Kingdom** info@wildcat-taconic.com
**Poland** biuro@4taconic.com

For queries in North America please visit www.4taconic.com or email info@4taconic.com

REACH COMPLIANCE RoHS