



Product Specification 6525-10

6525-10 is a red Silicone Rubber/Glass Fabric with Silicone adhesive & corrugated yellow liner. It is used where preparatory Grit blast is particularly heavy. Unlike some competitors' product, Taconic's 6525-10 has a liner, which makes it easier to remove. It is a Rolls Royce Approved product available in slit rolls format at required widths.

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		SILICONE		
Substrate Type		E-GLASS		
Total Weight of Substrate	g/m2	335		ISO 2286-2
% Coating of Substrate	%	63		
Substrate Thickness		N/A		
Adhesive Thickness	micron	75		ISO 2286-3
Total Product Thickness	micron	325		
Adhesive Strength	N/25,4mm	8	Typical	ISO 8510-2
		6	Minimum	
Operating Temperature	°Celsius	-73° to +230°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Please contact us for samples or a quotation

Taconic International Ltd
Ireland
www.taconic-ipd.com
info@taconic-ipd.com



Taconic France
France
www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany
www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom
www.taconic-ipd.com
info@wildcat-taconic.com

For queries in North America please visit www.4taconic.com or email info@4taconic.com



Taconic SP z.o.o
Poland
www.taconic-ipd.pl
biuro@4taconic.com

