Product Specification 7102 LSR Red

Taconic's 7102 LSR Red is glass fibre product coated with a red food approved liquid silicone. The high friction and release properties offer superior performance across a wide variety of food & industrial applications as well as excellent value. With its abrasion and flex resistant surface, excellent chemical resistance, superior dielectric and release properties and approved food contact, 7102 LSR Red is used in many food and bakery applications, conveyor belt and curtain material in industrial packaging applications. Standard width of 7102 LSR Red is 1000m.

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		**E-GLASS**		
Coating Type		**LSR**		
% Coating	%	**72**		ISO 2286-2
Total Coated Weight	g/m2	**395**	+/- 5%	ISO 2286-2
Nominal Thickness	mm	**265**		ISO 2286-3
Tensile Strength	%	**1100**	Typical Warp	ISO 1421
		1000	Minimum Warp	
		N/A	Typical weft	
		N/A	Minimum weft	
Colour		**Red**		
Operating Temperature	°Celsius	**-73° to +230°**		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.

QUALITY ISO 9001:2015 NSAI Certified
ENVIRONMENT ISO 14001:2015 NSAI Certified

Please contact us for samples or a quotation

Taconic International Ltd
Ireland
www.taconic-ipd.com
info@taconic-ipd.com

Taconic France
France
www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany
www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom
www.taconic-ipd.com
info@wildcat-taconic.com

Taconic SP z.o.o
Poland
www.taconic-ipd.pl
biuro@4taconic.com

For queries in North America please visit www.4taconic.com or email info@4taconic.com

Rev: 08/09 - 001