Product Specification 7208

Taconic's 7208 is a PTFE coated glass fibre belting product with a medium PTFE content. Specially developed for conveying applications where an imprint of the glass fabric is required on the end product, 7208 is used as a robust transport belt in many industries offering excellent value and performance. Other applications include use as gaskets & membranes in chemical plants. Standard width of 7208 is 2000mm

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		**E-GLASS**		
Coating Type		**PTFE**		
% Coating	%	**54**	+/-2%	
Total Coated Weight	g/sqm	**880**	+/-5%	
Nominal Thickness	microns	**450**		
Coating Adhesion Strength	N/5cm	**70**	Typical	ISO 2411
		55	Minimum	
Dielectric Breakdown	Volts	**3500**	Typical	BS 2782 part 2
		3000	Minimum	
Tensile Strength	N/5cm	**4000**	Typical Warp	ISO 1421
		3500	Minimum Warp	
		2500	Typical weft	
		2000	Minimum weft	
Tear Strength	N	**90**	Typical Warp	ISO 9073-4
		80	Minimum Warp	
		80	Typical weft	
		60	Minimum weft	
Operating Temperature	°Celsius	**-73° to +260°**		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.

QUALITY ISO 9001:2015 NSAI Certified
ENVIRONMENT ISO 14001:2015 NSAI Certified

Please contact us for samples or a quotation

Taconic International Ltd
Ireland
www.taconic-ipd.com
info@taconic-ipd.com

Taconic France
France
www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany
www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom
www.taconic-ipd.com
info@wildcat-taconic.com

Taconic SP z.o.o
Poland
www.taconic-ipd.pl
biuro@4taconic.com

For queries in North America please visit www.4taconic.com or email info@4taconic.com

REACH RoHS

Rev: 10/10 - 001