Product Specification 7255

Taconic's 7255 is a 2x2mm glass fibre product with a low coating of PTFE, used as a non-stick belting material for conveying materials in applications requiring airflow. The 2x2mm mesh size of 7255 offers a regulated airflow whilst applications include textile drying, conveying synthetic yarns through curing ovens, transporting printed textiles through drying ovens as well as carrying woven, non-woven and knitted fabrics through texturizing ovens. Other uses include dryer belts for curing paper and PVC materials in screen printing. In all cases, the advantages of 7255 open mesh belts include no mark-off, resistance to inks, controlled porosity, dimensional stability & temperature resistance to 260°C. Standard width of 7255 is 3200mm, though other dimensions may be available upon request.

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		**E-GLASS**		
Coating Type		**PTFE**		
% Coating	%	**26**	+/-2%	
Total Coated Weight	g/sqm	**445**	+/-5%	
Nominal Thickness	microns	**740**		
Tensile Strength	N/5cm	**1800**	Typical Warp	ISO 1421
		1500	Minimum Warp	
		N/A	Typical weft	
		N/A	Minimum weft	
Operating Temperature	°Celsius	**-73° to +260°**		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.

QUALITY ISO 9001:2015 NSAI Certified
ENVIRONMENT ISO 14001:2015 NSAI Certified

Please contact us for samples or a quotation

Taconic International Ltd
Ireland
www.taconic-ipd.com
info@taconic-ipd.com

Taconic France
France
www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany
www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom
www.taconic-ipd.com
info@wildcat-taconic.com

Taconic SP z.o.o
Poland
www.taconic-ipd.pl
biuro@4taconic.com

For queries in North America please visit www.4taconic.com or email info@4taconic.com

Rev: 06/09 - 004