



Product Specification 9054

Taconic's 9054 is a flexible PTFE coated glass fibre product with a high PTFE content. As a premium grade non-stick material with crease and tear properties, 9054 is ideal for use in the packaging industry as a belt or as edge reinforcement. In addition with its smooth surface and release properties, 9054 offers excellent value and performance. Standard widths of 9054 are 1000mm & 1500mm

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		E-GLASS		
Coating Type		PTFE		
% Coating	%	57	+/-2%	
Total Coated Weight	g/sqm	255	+/-5%	
Nominal Thickness	microns	127		
Coating Adhesion Strength	N/5cm	25	Typical	ISO 2411
		20	Minimum	
Dielectric Breakdown	Volts	2500	Typical	BS 2782 part 2
		2000	Minimum	
Tensile Strength	N/5cm	1400	Typical Warp	ISO 1421
		1250	Minimum Warp	
		N/A	Typical weft	
		N/A	Minimum weft	
Tear Strength	N	45	Typical Warp	ISO 9073-4
		35	Minimum Warp	
			Typical weft	
			Minimum weft	
Operating Temperature	°Celsius	-73° to +260°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Please contact us for samples or a quotation

Taconic International Ltd
Ireland
www.taconic-ipd.com
info@taconic-ipd.com



Taconic France
France
www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany
www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom
www.taconic-ipd.com
info@wildcat-taconic.com



Taconic SP z.o.o
Poland
www.taconic-ipd.pl
biuro@4taconic.com



For queries in North America please visit www.4taconic.com or email info@4taconic.com