



Product Specification **A7063**

Taconic's A7063 is a semi-conductive PTFE coated glass fibre product with a high PTFE content and silicone adhesive with a corrugated yellow backing liner. Mainly used as a high temperature release material in applications in the packaging, plastics and composite industries where semi-conductive properties are required, as well as a liner in mould release and roller covering applications, A7063 is seen as offering excellent value and superior performance. Standard widths of A7063 is 1000mm as well as slit rolls from 10mm and upwards.

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		SILICONE		
Substrate Type		E-GLASS		
Total Weight of Substrate	g/m2	296		ISO 2286-2
% Coating of Substrate	%	65		
Substrate Thickness	micron	138		
Adhesive Thickness	micron	60		ISO 2286-3
Total Product Thickness	micron	198		
Adhesive Strength	N/25,4mm	12	Typical	ISO 8510-2
		10	Minimum	
Operating Temperature	°Celsius	-73° to +260°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Please contact us for samples or a quotation

Taconic International Ltd
Ireland
www.taconic-ipd.com
info@taconic-ipd.com



Taconic France
France
www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany
www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom
www.taconic-ipd.com
info@wildcat-taconic.com

Taconic SP z.o.o
Poland
www.taconic-ipd.pl
biuro@4taconic.com



For queries in North America please visit www.4taconic.com or email info@4taconic.com

