Product Specification AA02SK SW

Taconic's AA02SK SW is a 2 thou (0.05mm) thick skived, virgin PTFE product with acrylic adhesive, self wound (without liner). Mainly used as a high temperature release material in the automotive, aerospace and composite industries as well as in cable wrap applications, AA02SK is seen as offering excellent value and superior performance. Standard width of AA02SK is 600mm, with availability also as slit rolls from 12.5mm and upwards.

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		**ACRYLIC**		
Substrate Type		**PTFE FILM**		
Total Weight of Substrate	g/m2	**N/A**	+/-12	ISO2286-2
% Coating of Substrate		**N/A**		
Substrate Thickness	micron	**50**		
Adhesive Thickness	micron	**30**		ISO2286-3
Total Product Thickness	micron	**80**		
Adhesive Strength	N/25,4mm	**8**	Typical	ISO8510-2
		6	Minimum	
Operating Temperature	°Celsius	**-73° to +180°**		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.

QUALITY ISO 9001:2015 NSAI Certified
ENVIRONMENT ISO 14001:2015 NSAI Certified

Please contact us for samples or a quotation

Taconic International Ltd
Ireland
www.taconic-ipd.com
info@taconic-ipd.com

Taconic France
France
www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany
www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom
www.taconic-ipd.com
info@wildcat-taconic.com

Taconic SP z.o.o
Poland
www.taconic-ipd.pl
biuro@4taconic.com

For queries in North America please visit www.4taconic.com or email info@4taconic.com

TÜV SÜD ISO 9001
REACH COMPLIANCE RoHS