



Product Specification Tacfuse 10

Taconic's Tacfuse 10 is a black, anti-static PTFE coated glass fibre product with a high PTFE content which offers excellent value and performance. The smooth surface of Tacfuse 10 lends itself for use as a non-stick, semi conductive belting material in the fuse press industry where excellent release, non-marking and anti-static properties are crucial during the continuous lamination of reinforced panels of collars and cuffs. Standard widths of Tacfuse 10 are 1000mm, 1500mm, 2000mm, 2400mm, 2600mm & 2750mm.

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		E-GLASS		
Coating Type		PTFE		
% Coating	%	58	+/-2%	
Total Coated Weight	g/sqm	490	+/-5%	
Nominal Thickness	microns	235		
Coating Adhesion Strength	N/5cm	45	Typical	ISO 2411
		30	Minimum	
Tensile Strength	N/5cm	2200	Typical Warp	ISO 1421
		2000	Minimum Warp	
		1700	Typical weft	
		1300	Minimum weft	
Tear Strength	N	40	Typical Warp	ISO 9073-4
		25	Minimum Warp	
		30	Typical weft	
		23	Minimum weft	
Surface Resistivity	Mega Ohms	10	Maximum	EN 61340-2-3
Operating Temperature	°Celsius	-73° to +260°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Please contact us for samples or a quotation

Taconic International Ltd
Ireland

www.taconic-ipd.com
info@taconic-ipd.com



Taconic France
France

www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany

www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom

www.taconic-ipd.com
info@wildcat-taconic.com



Taconic SP z.o.o
Poland

www.taconic-ipd.pl
biuro@4taconic.com



For queries in North America please visit www.4taconic.com or email info@4taconic.com