



Product Specification Tacfuse 14

Taconic's Tacfuse 14 is a black anti-static PTFE coated glass fibre product with a medium PTFE content. Specially developed as a belt conveyor material with a smooth, semi-conductive high release surface, applications for Tacfuse 14 include, fuse press, solar panel and high temperature pressing of construction materials offering excellent value and efficiency. Standard widths of Tacfuse 14 are 1000mm, 1500mm, 2000mm, 2400mm, 2600mm & 3300mm.

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		E-GLASS		
Coating Type		PTFE		
% Coating	%	57	+/-2%	
Total Coated Weight	g/sqm	680	+/-5%	
Nominal Thickness	microns	340		
Coating Adhesion Strength	N/5cm	70	Typical	ISO 2411
		40	Minimum	
Tensile Strength	N/5cm	4000	Typical Warp	ISO 1421
		3000	Minimum Warp	
		2500	Typical weft	
		2000	Minimum weft	
Tear Strength	N	90	Typical Warp	ISO 9073-4
		40	Minimum Warp	
		70	Typical weft	
		40	Minimum weft	
Surface Resistivity	Mega Ohms	10	Maximum	EN 61340-2-3
Operating Temperature	°Celsius	-73° to +260°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Please contact us for samples or a quotation

Taconic International Ltd
Ireland
www.taconic-ipd.com
info@taconic-ipd.com

Taconic France
France
www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany
www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom
www.taconic-ipd.com
info@wildcat-taconic.com

Taconic SP z.o.o
Poland
www.taconic-ipd.pl
biuro@4taconic.com



For queries in North America please visit www.4taconic.com or email info@4taconic.com

