Product Specification Tacweld 69 Green

Taconic's Tacweld 69 Green is a premium PTFE coated glass fibre product with a super smooth coating. Used as a superior release material in the uPVC industry, its smooth surface and strength offers excellent value & performance. Key characteristics of Tacweld 69 Green include superior release, temperature & chemical resistance and easy cleaning. Standard width of Tacweld 69 Green is 1000mm.

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		**E-GLASS**		
Coating Type		**PTFE**		
% Coating	%	**66**	+/-2%	
Total Coated Weight	g/sqm	**315**	+/-5%	
Nominal Thickness	microns	**143**		
Coating Adhesion Strength	N/5cm	**22**	Typical	ISO 2411
		15	Minimum	
Dielectric Breakdown	Volts	**3000**	Typical	BS 2782 part 2
		2500	Minimum	
Tensile Strength	N/5cm	**1300**	Typical Warp	ISO 1421
		900	Minimum Warp	
		1300	Typical weft	
		900	Minimum weft	
Tear Strength	N	**20**	Typical Warp	ISO 9073-4
		10	Minimum Warp	
		20	Typical weft	
		10	Minimum weft	
Operating Temperature	°Celsius	**-73° to +260°**		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.

QUALITY ISO 9001:2015 NSAI Certified
ENVIRONMENT ISO 14001:2015 NSAI Certified

Please contact us for samples or a quotation

Taconic International Ltd
Ireland
www.taconic-ipd.com
info@taconic-ipd.com

Taconic France
France
www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany
www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom
www.taconic-ipd.com
info@wildcat-taconic.com

Taconic SP z.o.o
Poland
www.taconic-ipd.pl
biuro@4taconic.com

For queries in North America please visit www.4taconic.com or email info@4taconic.com

Rev: 05/21 - 002